

(12) NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES
PATENTWESENS (PCT) VERÖFFENTLICHTE INTERNATIONALE ANMELDUNG

(19) Weltorganisation für geistiges Eigentum
Internationales Büro



(43) Internationales Veröffentlichungsdatum
4. November 2004 (04.11.2004)

PCT

(10) Internationale Veröffentlichungsnummer
WO 2004/094083 A3

(51) Internationale Patentklassifikation⁷: B21J 5/12,
B21K 1/30

(21) Internationales Aktenzeichen: PCT/DE2004/000840

(22) Internationales Anmeldedatum:
22. April 2004 (22.04.2004)

(25) Einreichungssprache: Deutsch

(26) Veröffentlichungssprache: Deutsch

(30) Angaben zur Priorität:
103 18 178.4 22. April 2003 (22.04.2003) DE

(71) Anmelder (für alle Bestimmungsstaaten mit Ausnahme von
US): NEUMAYER HOLDING GMBH [DE/DE]; Wil-
helm-Zangen-Strasse 9, 77756 Hausach (DE).

(72) Erfinder; und

(75) Erfinder/Anmelder (nur für US): VOGEL, Manfred
[DE/DE]; Bernhardshöfe 113, 77876 Kappelrodeck (DE).


(74) Anwalt: HAFT, VON PUTTKAMER, BERNGRU-
BER, KARAKATSANIS; Franziskanerstrasse 38, 81669
München (DE).

(81) Bestimmungsstaaten (soweit nicht anders angegeben, für
jede verfügbare nationale Schutzrechtsart): AE, AG, AL,
AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Fortsetzung auf der nächsten Seite]

(54) Title: METHOD FOR PRODUCING A CUP-SHAPED ANNULAR PART HAVING AN INNER TOOTHING, A
CUP-SHAPED PREFORM AND A CUP-SHAPED ANNULAR PART

(54) Bezeichnung: VERFAHREN ZUR HERSTELLUNG EINES NAPFFÖRMIGEN RINGTEILES MIT INNENVERZAH-
NUNG, NAPFFÖRMIGE VORFORM UND NAPFFÖRMIGES RINGTEIL



(57) Abstract: The invention relates to a
method for producing a cup-shaped annu-
lar part (2') having an inner toothing. The
invention also relates to a cup-shaped pre-
form and to a cup-shaped annular part.

(57) Zusammenfassung: Die Erfindung
betrifft ein Verfahren zur Herstellung
eines napfförmigen Ringteiles (2') mit
Innenverzahnung. Die Erfindung betrifft
ferner eine napfförmige Vorform und ein
napfförmiges Ringteil.

WO 2004/094083 A3



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) **Bestimmungsstaaten** (soweit nicht anders angegeben, für jede verfügbare regionale Schutzrechtsart): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), eurasisches (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Veröffentlicht:

- mit internationalem Recherchenbericht
- vor Ablauf der für Änderungen der Ansprüche geltenden Frist: Veröffentlichung wird wiederholt, falls Änderungen eintreffen

- (88) **Veröffentlichungsdatum des internationalen Recherchenberichts:**

20. Januar 2005

Zur Erklärung der Zweibuchstaben-Codes und der anderen Abkürzungen wird auf die Erklärungen ("Guidance Notes on Codes and Abbreviations") am Anfang jeder regulären Ausgabe der PCT-Gazette verwiesen.

3/pet 1

2005

Method For Producing A Cup-Shaped Annular Part Having An Inner
Toothings

The present invention relates to a method for producing a cup-shaped annular part having an inner toothings.

Usually, such cup-shaped annular parts having an inner toothings are produced by producing the teeth of the inner toothings on the inner wall of an annular element by using a process of striking and/or a different machining operation. If such annular parts that are used, for example in automatic gearboxes, as internal geared wheels for planetary gears, are required to have a mechanical connection to their longitudinal central axis, they are usually connected to a separately produced hub part so that the result is an annular part with the shape of a cup on the whole. The annular part is connected to the hub part, for example by using a plug-in connection or a screw connection.

In the older patent application DE 100 54 399.5, a method and a device for producing a single-piece cup-shaped annular part having an inner toothings is described in which a cup-shaped preform is inserted between a counterholder that can be activated using a hydraulic piston and a pressure punch that can be activated using an additional hydraulic piston. A mandrel part that has an external profile that corresponds to the toothings to be produced on the inner wall of the preform is inserted into the interior space of the preform.

In a forming operation, the counterholder is pressed against the floor of the preform and the annular pressure punch is pressed against the front surface of the cylindrical edge of the preform. In order to prevent the material of the preform from giving way and/or flowing radially outwards, the preform is surrounded by a

drawing ring that exerts a counter pressure in the radial direction.

The objective of the present invention is to specify a method for producing a priceworthy, cup-shaped annular part that is designed as a single piece and consists of an annular element having an inner toothing and a hub part. Said method enables the inner toothing of the annular element to extend up to the level of the floor space of the hub part using a comparatively smaller discharge area. As a result, for example in the later application in an automatic gear, spur gear wheels, particularly planetary wheels, can extend practically up to the level of this floor space and can comb with the inner toothing of the annular element even in this area.

The present invention achieves this objective and is characterized in that at least some of the following features are implemented into the invention.

- 1) A cup-shaped preform having an annular element and a hub part are arranged in a matrix part.
- 2) A punch part that has an outer toothing on its outer wall that corresponds to the inner toothing to be produced in the annular element is inserted into the interior space of the preform.
- 3) With the aid of an annular punch part, pressure is exerted in a forming step on the front surface of the open end of the preform by carrying out a relative movement between the matrix part and the punch part.
- 4) An annular groove is provided in the floor space of the hub part in the corner region between the inner surface of the annular element and the floor space of the hub part.

- 5) Pressure is exerted on the front surface of the open end of the preform so that material of the preform flows across the punch part into the area of the groove.

The essential advantage of the present invention is that the teeth of the inner toothing of the annular element of the cup-shaped annular part can extend practically up to the level of the floor space of the hub part so that spur gear wheels, particularly planetary wheels can comb with the inner toothing up to the level of the floor space of the hub part. This enables a design that is very compact in the axial direction. Furthermore, the individual teeth of the annular parts produced according to the present method, particularly even in the region of the floor space of the hub part are designed to be extremely sharp-edged and precisely in line with the contour. For this purpose, a preform is used according to the present method in which an indentation and/or a groove is arranged in the corner region between the floor space of the hub part and the inner surface of the annular wall of the annular element. This enables the production of the inner toothing directly up to the level of the floor space using a minimum discharge area during the forming process since material can flow across the level of the hub part and into the indentation and/or groove during the forming process. Therefore, spur gear wheels, for example planetary wheels can extend closer to the floor space of the hub part. Thus, the axial overall length of the present annular part is reduced still further.

For an especially accurate configuration of the teeth, in a particularly preferred embodiment of the present invention, the groove is inserted into the preform in such a way that its radially outer side forms an extension of the inner surface of the annular element of the preform. In the same forming step, an outer toothing can be produced on the outer side of the annular

part with particular ease and advantage due to the fact that the matrix part has an inner toothing on its inner surface that corresponds to the outer toothing. For producing an annular part having an axle pin, it is possible to use a matrix part that has a central recess for accommodating the axle pin. For producing an annular part having a central borehole in the hub part, it is possible to use a preform that has a central borehole in the hub part. A drawing ring can be used that surrounds the region of the annular element of the preform that projects over the matrix part in order to exert a radial counter pressure during the forming process. Here, the drawing ring can be designed as a single piece with the matrix part.

The cup-shaped preform for implementing the method according to the present invention has an annular groove in the end area between the annular element and the floor space of the hub part, whereby the radially outer side of the groove can form an extension of the inner surface of the ring element for the purpose of an accurate configuration of the teeth.

The present invention and its embodiments are explained more elaborately in the following description by reference to the figures, of which:

Figure 1 is a schematic illustration of a device for implementing the method according to the present invention for producing an annular part;

Figure 2 illustrates an annular part that has been produced according to a preferred embodiment of the present invention; and

Figures 3 to 6 illustrate additional embodiments of the present invention.

According to figure 1, the device for producing an annular part 2' (figure 2) according to the present method essentially has a matrix part 1 that can accommodate a cup-shaped preform 2 having a hub part 11 and an annular element 3 that extends perpendicularly to the hub part. Furthermore, the matrix part has a punch part 4 that dips into the interior space of the preform 2 and an annular pressure punch 5. On its outer wall, the punch part 4 has an outer toothing 7 that corresponds to the inner toothing 6 to be produced in the annular element 3.

The matrix part 1 can be provided with a single-piece or a two-piece design so that it can accommodate the cup-shaped preform 2. In order to prevent the material of the preform in the upper region from giving way and in order to bring about a radial flow of the material into the toothing region, a schematically illustrated drawing ring 20 that is known per se is provided. Said drawing ring surrounds the region of the annular element 3 of the preform 2 that projects over the matrix part 1. Moreover, said drawing ring exerts a radial counter pressure during the forming process. This drawing ring 20 can also be designed with the matrix part 1 as a single piece.

In order to implement the forming process, a preform 2 is first inserted into the interior space of the matrix part 1. Thereafter, the punch part 4 is inserted with its outer toothing 7 into the interior space of the preform 2. Then the matrix part 1 and/or the annular pressure punch 5 that rests against the front surface of the open end of the preform 2, are moved relative to one another e.g. hydraulically so that the preform 2 is formed into the annular part 2' (Figure 2) to be produced, whereby the outer toothing 7 of the punch part 4 is pictured with a sharp edge as the inner toothing 6 in the inner wall of the annular element 3' of the annular part 2'. For this purpose, it is particularly important for the outer toothing 7 of the punch

part 4 to extend up to the front surface 14 of the punch part 4. This ensures that the outer toothing 7 can be guided up to the floor space 13 during the insertion of the punch part 4 into the preform 2. Therefore, in the subsequent forming process, in which a relative movement is carried out between the pressure punch 5 and the matrix part 1, the material of the preform 2 flows into the outer toothing 7 of the punch part 4 and into the corner region between the annular element 3 and its floor space 13 so that the ends of the inner toothing 6 are pictured with shape accuracy in the corner region of the formed annular part 2' between the floor space 13' of the hub part 11' and the inner surface 12' of the annular element 3'. Figure 2 illustrates the annular part 2' that is produced in this manner from the preform 2. In other words, by using the present method, it is feasible that the inner toothing 6 extends up to the said floor space 13' of the annular part 3' exactly and with shape accuracy.

At this juncture, it must be pointed out that the toothings 6, 7 can be axially extending toothings as illustrated or also helical toothings.

According to figure 3, the preform 2 has an annular indentation and/or groove 9 according to the present invention in the corner region between the inner surface 12 of the annular wall of the annular element 3 and the floor space 13 of the hub part 11. Due to this indentation and/or groove, it is feasible that when forming the preform 2 into the annular part 2', the inner toothing 6 produced in the annular element 3' extends up to the level of the floor space 13' of the hub part 11'. This is because the extruded and/or flowing material of the preform 2 can flow across the punch part 4 and into the region of the groove 9. In this connection, it is particularly important for the radially outer side 9' of the groove 9 to form the most accurate extension

possible of the inner surface 12 of the annular element 3 of the preform 2.

Figure 4 illustrates an additional preform 2 and a matrix part 1 for producing a cup-shaped annular part 2' having a molded axle pin 16. In this case, the matrix part 1 has a central recess 18 that is provided with a design, which is preferably complementary to the shape of the axle pin 16 and can accommodate the latter during the forming process.

Figure 5 illustrates an additional embodiment of the present invention in which the preform 2 (and therefore even the annular part 2' produced from it) has a central borehole 17 in the hub part 11.

Finally, figure 6 illustrates an embodiment of the present invention in which, in addition to the inner toothing 6, an outer toothing is simultaneously molded on the outer side of the annular element 3 in one and the same forming step. For this purpose, the matrix part 1 has a corresponding inner toothing 19 on its inner surface. The outer toothing can have the shape of a straight toothing or a helical toothing as well as a plug-in toothing and a meshing toothing.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/DE2004/000840

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B21J5/12 B21K1/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B21J B21K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 014, no. 119 (M-0945), 6 March 1990 (1990-03-06) -& JP 01 317653 A (HONDA MOTOR CO LTD), 22 December 1989 (1989-12-22) abstract; figures 1,2	1, 2, 4-10
A	PATENT ABSTRACTS OF JAPAN vol. 018, no. 079 (M-1557), 9 February 1994 (1994-02-09) -& JP 05 293586 A (YAMAKAWA IND CO LTD; others: 01), 9 November 1993 (1993-11-09) abstract; figures 1-7	1, 6, 7
A	DE 100 54 399 A (FORSCHUNGSGESELLSCHAFT UMFORMT) 27 June 2002 (2002-06-27) cited in the application figures 1,2	1, 6, 7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the International filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

28 October 2004

Date of mailing of the international search report

08/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ritter, F

INTERNATIONAL SEARCH REPORT

International Application No
PCT/DE2004/000840

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 100 21 189 A (HAUK STEFAN) 25 January 2001 (2001-01-25) column 3, line 27 - line 32 -----	1,3
X	DE 36 39 739 A (HONDA MOTOR CO LTD) 1 June 1988 (1988-06-01) column 5, line 3 - line 52; figures 1,4,5 -----	8,10
A	EP 0 955 110 A (LEICO WERKZEUGMASCHB GMBH & CO) 10 November 1999 (1999-11-10) column 11, line 26 - line 45; figure 4 -----	1
X		8,9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DE2004/000840

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 01317653	A	22-12-1989	JP 1857149 C	07-07-1994
			JP 5063256 B	10-09-1993
JP 05293586	A	09-11-1993	JP 2050489 C	10-05-1996
			JP 7085823 B	20-09-1995
DE 10054399	A	27-06-2002	DE 10054399 A1	27-06-2002
			AU 1584602 A	15-05-2002
			WO 0236287 A1	10-05-2002
			EP 1330320 A1	30-07-2003
			JP 2004512956 T	30-04-2004
			US 2004016281 A1	29-01-2004
DE 10021189	A	25-01-2001	DE 10021189 A1	25-01-2001
DE 3639739	A	01-06-1988	DE 3639739 A1	01-06-1988
EP 0955110	A	10-11-1999	DE 19830816 A1	11-03-1999
			CA 2271115 A1	07-11-1999
			DE 59909081 D1	13-05-2004
			EP 0955110 A2	10-11-1999
			JP 3202204 B2	27-08-2001
			JP 2000202556 A	25-07-2000
			US 6227024 B1	08-05-2001